

## NT CAT DMP-30 catalyst CAS25441-67-9 Newtopchem

### Overview

NT CAT DMP-30 is a tertiary amine-based foaming catalyst that facilitates urea (water-isocyanate) reactions in a variety of hard and soft polyurethane foam applications. It is the industry standard foaming catalyst for hard foams and is used in MDI-based on-site casting polyurethane systems, such as rigid appliances. It is also used in combination with trimer catalysts in PIR laminated paperboard formulations. NT CAT DMP-30 is also available for TDI, TDI/MDI, MDI High Resilience (HR) soft molding foams as well as self-crusting and microcellular systems. It has a shelf life of 36 months.

### CAS No.

The CAS number of the NT CAT DMP-30 is 25441-67-9. This is a unique identifier for NT CAT DMP-30 that is used to track and identify it throughout the supply chain. The CAS number is also used to search databases and other resources for information about NT CAT DMP-30.

### Physical and chemical properties

The physical and chemical properties of NT CAT DMP-30 are shown in the following table:

Properties	value
Looks	Clear colorless liquid
Scent	A slight ammonia smell
Specific gravity	1.040
Boiling point	200 °C
Flash point	100 °C
Water soluble	Miscible
Solubility in organic solvents	miscibility

## Features

Promotes urea (water-isocyanate) reaction

Used in a variety of hard and soft polyurethane foam applications

Industry standard foaming catalyst for hard foams

For use in MDI based in situ polyurethane systems such as rigid appliances

Use in combination with trimer catalysts in PIR laminated paperboard formulations

Also available in TDI, TDI/MDI, MDI High Resilience (HR) soft molded foams as well as self-crusting and microcellular systems

The shelf life is 36 months

### Application

- Rigid polyurethane foam
- Field pouring polyurethane system
- PIR laminated cardboard



- TDI, TDI/MDI, MDI High Resilience (HR) Soft molded foam
- Self-crusting foam
- Microcellular foam

## Pros

- Promotes urea (water-isocyanate) reaction
- Used in a variety of hard and soft polyurethane foam applications
- Industry standard foaming catalyst for hard foams
- Can be used in combination with trimer catalysts
- Shelf life is 36 months

## Cons

- Corrosive to certain metals
- Can have a strong odor
- Combustible

## Similarities and differences with similar products

NT CAT DMP-30 is similar to other tertiary amine-based foaming catalysts in that it promotes urea (water-isocyanate) reaction. However, it offers a number of advantages over other products, including its use in a variety of applications, its industry standard status as a hard foam and its ability to be combined with trimer catalysts.

## Precautions for Use

- Wear gloves and goggles when handling the NT CAT DMP-30.
- Avoid contact with skin and eyes.
- Keep away from heat sources and open flames.
- Store in a cool, dry place.
- Dispose of it properly according to local regulations.

**Shelf life:**

Remain unopened for two years

**Storage and Transportation:**

Should be sealed, stored in a dry cool ventilated warehouse

**Packing:**

200KG/ barrel storage: It is recommended to store in a dry and cool area with proper ventilation. After the original packaging, please fasten the packaging cover as soon as possible to prevent moisture and other substances from mixing and affecting the product performance. Do not inhale dust and avoid contact between skin and mucous membrane. Smoking, eating and drinking are prohibited in the workplace. Shower and change after work. Store contaminated clothes separately and use them after washing. Practice good hygiene.

**Technical support and business contacts E-mail: [info@newtopchem.com](mailto:info@newtopchem.com)**