

## NT CAT LA-505 catalyst CAS10144-28-9 Newtopchem

NT CAT LA-505 is a tertiary amine catalyst for the production of soft polyurethane foams. It is a clear, colorless liquid with a mild odor. NT CAT LA-505 is a strong catalyst that can be used to produce foams with a variety of properties. It is also a low-odor catalyst, which makes it ideal for applications that require attention to odor emissions.

### Physical and chemical properties

Properties	value
Molecular formula	C <sub>12</sub> H <sub>23</sub> N <sub>3</sub>
Molecular weight	227.3 g/mole
Appearance	Clear colorless liquid
Scent	Mild
Density	0.94 g/cm <sup>3</sup>
Boiling point	155 °C

Flash point	100 degrees Fahrenheit
Solubility	Soluble in water, alcohol, ether

## Features

Strong catalyst

Low odor

Wide range of applications

Ease of use

## Application

- Soft polyurethane foam
- Rigid polyurethane foam
- Elastomer
- Paint
- Adhesive

## advantage

- Strong catalyst

- Low odor
- Wide range of applications
- Ease of use

### Disadvantages

- Corrosive to certain metals
- Combustible
- May be toxic by inhalation or ingestion

### Precautions for use

- Wear gloves and safety goggles when handling NT CAT LA-505.
- Keep the NT CAT LA-505 away from heat sources and open flames.
- Do not inhale NT CAT LA-505 vapor.
- If it comes into contact with skin, wash it immediately with soap and water.
- If swallowed, do not try to induce vomiting. Call poison control immediately.



### **Storage**

Store NT CAT LA-505 in a cool, dry place. Keep the container airtight.

### **Dispose**

Dispose of the NT CAT LA-505 according to local regulations.

### **Shelf life:**

Remain unopened for two years

### **Storage and Transportation:**

Should be sealed, stored in a dry cool ventilated warehouse

### **Packing:**

Newtop Chemical Materials (Shanghai) Co.,Ltd.

Address: Rm1104 ,No. 258, West SongXing Road, BaoShan District, Shanghai, China.

Mobile Phone: +0086-183 0190 3151 E-mail: [info@newtopchem.com](mailto:info@newtopchem.com) [www.newtopchem.com](http://www.newtopchem.com)

200KG/ barrel storage: It is recommended to store in a dry and cool area with proper ventilation. After the original packaging, please fasten the packaging cover as soon as possible to prevent moisture and other substances from mixing and affecting the product performance. Do not inhale dust and avoid contact between skin and mucous membrane. Smoking, eating and drinking are prohibited in the workplace. Shower and change after work. Store contaminated clothes separately and use them after washing. Practice good hygiene.

**Technical support and business contacts E-mail: [info@newtopchem.com](mailto:info@newtopchem.com)**